134855
NUMBER
DOCUMENT

	0.101.10		OLIDA IES		
115	PURLIC	I ANII)	CHRVEY	MINIMENI	RFCORD
U. J.	I ODLIC	LAIT	COLLAFI	MONUMENT	

	V	_	12	,	1	3
Index	No					

State of Wisconsin County of Forest William B. Cochrane , do hereby certify that on the lst day of July , 19 87, I found	History of original corner establishment:			
	Original Government Survey in 1865 by William E. Daugherty. Dependent Resurvey in 1925 by Arthur Brown. At proportionate distance, set an iron post, 3 feet long, 2 inches in diameter, 28 inches in the ground, with a brass cap marked; T40N, R14E, MC, S28, S33, 1925. Blazed and scribed the following new bearing trees;			
evidence of the MC on East Shore of Main eurner of Line Lake Bet. Secs. 28 Township and 33 , North, Range T40N R14E , Fourth Principal Meridian,	W. Pine 5" N76°00'E 22 1ks. W. Pine 6" S54°45'E 37 1ks.			
as described hereon; and that from this evidence	Description of corner evidence found:			
I established a new monument and accessories as described hereon to perpetuate the original location of this corner.	Found the monument as described, 6 inches below the surface of MainLine Lake, from which the following bear;			
Resident witnesses:	W. Pine(Snag w/scribe) N76°00'E 14.52 feet			
	Description of monument and accessories I established to perpetuate the original location of this corner. No bearing trees available. Set a Steel Sign Post East 8.00 feet			
SECTION 33	Dated at			
O = Corner monument restored.	ByDeputy			

Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (d), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 2 of the witness monuments shown on the drawing in (d), above. e)

See drawing below.

Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

Restored through acceptance of a found perpetuated location.

(g&h) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning in determining the corner location?

W. Pine(Snag w/scribe) N76°E, 14.52 feet 1925 BT

Affix Land Surveyor Scal

WILLIAM B.

COCHRANE

WISC. WISC. SURVEY

Meander Corner S33

S28

Steel Sign Post East, 8.00 feet

William B. Cochrane (i) ltype or print name; certify that the corner location shown on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief,

Cochrane

Jan. 12

Survey requested by:

William B.

clevare District Ranger

Date